

Appendix B

Specification Support from the Instant Disclosure and Applicants' 1981 Priority Disclosure

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
67. A method for controlling the display of video information on a remote display	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2. Page 37 line 26 to page 38 line 8.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205; In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.
		This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204. The viewer then sees a microcomputer generated graphic of his own stocks' performance ...	Page 26 lines 4-11.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...
	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and	Page 337 lines 1-8.	Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 10 lines 24-28.	signal processor, 96, ... FIGS. 3A, 3B and 3C illustrates one instance of such use. FIGS. 3A, 3B, and 3C illustrate the use of Signal Processing Apparatus and Methods at a cable television system "head end" transmission facility that cablecasts several channels of television programming.	Page 324 lines 18-21.	distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to signal processor, 96, ... Fig. 6 illustrates Signal Processing Apparatus and Methods at an intermediate transmission station that is a cable television system "head end" and that cablecasts several channels of television programming.
	Column 19 lines 43-44.	... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 21 lines 23-24.	... instruction signals embedded in the "Wall Street Week" programming transmission.
an executable program	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			<p>Page 44 lines 14-17.</p> <p>Page 26 lines 20-28.</p>	<p>"program instruction set.")</p> <p>A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)</p>
from a source	Column 10 lines 30-39.	<p>The facility receives programming from many sources. Transmissions may be received from satellites by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56.</p> <p>Microwave transmissions can be received by microwave antenna, 57, and television video and audio receivers, 58 and 59.</p> <p>Conventional TV broadcast transmissions can be received by antenna, 60, and TV demodulator, 61. Other electronic programming input means, 62, can receive programming transmissions.</p>	Page 324 lines 23-31.	<p>The station receives programming from many sources. Transmissions are received from a satellite by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions are received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions are received by antenna, 60, and TV demodulator, 61. Other electronic programming transmissions are received by other programming input means, 62.</p>
over a cable network to	Column 10 lines 43-47.	<p>... and/or to equipment that outputs them over various channels to the cable system's field distribution system, 93, which equipment includes here cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92.</p>	Page 325 lines 1-4.	<p>... apparatus that outputs said transmissions over various channels to the cable system's field distribution system, 93, which apparatus includes cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92.</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
a remote control processor, said remote control processor having	Column 17 lines 47-53.	FIG 6 illustrates one possible configuration of equipment in a home or office or other television and/or radio receiving site. Consideration of FIGS. 6F and 6G is facilitated by consideration, first, of individual examples of the types of co-ordinated presentations that the signal apparatus and methods described here can permit.	Page 390 lines 30-35.	Fig. 7 exemplifies one embodiment of an ultimate receiver station; is a subscriber station in the field distribution system, 93, of the intermediate transmission station of Fig. 6; and may be a home, an office, a theater, a hotel, or any other station where programming such as television or radio is displayed to persons.
	Column 19 lines 45-49.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205 ...	Page 396 lines 8-10.	Features, benefits, and modes of operation of the station of Fig. 7 are demonstrated in the following individual examples.
			Page 451 lines 6-7.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, ...
			Page 23 line 35 to page 24 line 4.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series.
			Page 37 line 26 to page 38 line 8.	In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.
			Page 24 lines 5-6.	Microcomputer, 205, evaluates the initial signal word or words which instruct it to ...
			Page 451 lines 7-9.	... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to ...

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>information and said ... enable-WSW-on-CC13 ...</p> <p>Said instructions contain one instance, and ... program-unit-of-interest information that is preprogrammed at said microcomputer, 205, contains a second instance of specific-WSW information, <i>which second instance reflects the wish of the subscriber of said station to view (or record) said "Wall Street Week" program when said program is transmitted.</i> Automatically, microcomputer, 205, compares said one instance to said</p> <p>program-unit-of-interest information and determines a match with said second instance.</p> <p>Determining a match causes</p> <p>microcomputer, 205, automatically to input said please-fully-enable-WSW</p> <p>-on-CC13-at-particular- 8:30 information to the controller, 20.</p> <p>Receiving said please-fully-enable-WSW-on-CC13-at- particular-8:30 information causes controller, 20, in a predetermined fashion, to prepare particular apparatus ...</p> <p>...to cause selected apparatus of said station--cable converter box, 201, ... to receive the transmission of cable channel 13;</p> <p>...</p> <p>Then, automatically, controller, 20, causes a selected tuner, 214, to tune to the frequency of cable channel 13, thereby causing its associated converter box, 201, to convert its...</p> <p>...to cause selected apparatus of said station--cable converter box, 201, ... to receive the transmission of cable channel 13;</p> <p>...</p> <p>In due course, while scanning sequentially all channels in the fashion of example #5, the apparatus of the signal processor, 200, of the</p>
			Page 439 lines 9-15.	
			Page 295 lines 6-8.	
			Page 439 lines 9-15.	
	Column 19 lines 14-15.	... pass all program and channel identifiers on all programing being cablecast on the multi-channel system.	Page 435 lines 16-18.	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			<p>station of Fig. 7 and 7C ...</p> <p>Via a conventional multi- channel cable transmission, in a fashion well known in the art, four channels of conventional television programming and two conventional FM radio signals are inputted to a first alternate contact of switch, 1, and to mixer, 2.</p> <p>Example #5 begins with the embedding and transmitting, at the remote station that originates the "Wall Street Week" broadcast, of the first message of the "Wall Street Week" program ...</p> <p>Then, in a predetermined fashion, control processor, 39J, determines that said first command contains subject matter meter-monitor information causing said control processor, 39J, to transmit a message that consists of ... execution segment information that is addressed to microcomputer, 205, (and that causes microcomputer, 205, to process the information of the meter- monitor segment immediately following said execution segment information as new programming now being transmitted on the channel of the channel mark of said meter-monitor segment)</p> <p>then meter-monitor segment information that includes the "program unit identification code" and subject matter information of said first command and the channel mark of cable channel 13 ... (Said message whose transmission is caused by receiving said first command enables microcomputer, 205, in a fashion described more fully below, to tune automatically to receive the program that said "program unit identification code" identifies if said program is of interest, ...</p> <p>All eight of said messages are commands.</p>	
	Page 248 lines 22-26 from example #5.		<p>Page 250 lines 13-16 from example #5.</p> <p>Page 252 lines 15-35 from example #5.</p>	
			Page 267 lines 20-28	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			from example #5.	The 1st- and 3rd-new-program-message (#5) and the 1st-new-radio-program- message (#5) signals are addressed to microcomputer, 205. Each informs said microcomputer of new programming transmissions to which said microcomputer can tune appropriate station receiver and display apparatus in fashions described below. (Hereinafter said commands are called "guide commands" because they can guide station control apparatus to desired programming.)
at said remote control processor;	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.") A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a
			Page 44 lines 14-17.	
			Page 26 lines 20-28.	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
storing said executable program at said remote control processor in said storage device; and	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
			Page 44 lines 14-17.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a
			Page 26 lines 20-28.	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
executing said executable program at said remote control processor,	Column 19 line 64 to column 20 line 1.	This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204. The viewer then sees a microcomputer generated graphic of his own stocks' performance ...	Page 26 lines 4-10.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the ...
said downloaded executable program receiving	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE"

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p> <p>A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)</p>
			<p>Page 44 lines 14-17.</p> <p>Page 26 lines 20-28.</p>	
messages	Column 2 lines 63-64.	(The term "signal unit" hereinafter means one complete signal instruction or information message unit.	Page 14 lines 26-27.	(The term "signal unit" hereinafter means one complete signal instruction or information message unit.
from said cable head end	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and signal processor, 96, ...	Page 337 lines 1-8.	Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to signal processor, 96, ...

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 19 lines 43-44.	... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 21 lines 23-24.	... instruction signals embedded in the "Wall Street Week" programming transmission.
to effect operation of	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;
			Page 37 line 26 to page 38 line 8.	In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.
		This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204. The viewer then sees a microcomputer generated graphic of his own stocks' performance ...	Page 26 lines 4-11.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 20 lines 5-7.	... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.	Page 27 lines 7-9 and Page 451 line 22 to Page 452 line 5.	<p>Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.</p> <p>Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p> <p>In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.</p>
said downloaded program,	Column 19 lines 48-53.	These signals instruct microcomputer, 205, to	Page 23 line 35 to page 24 line 16.	<p>Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		generate several graphic video overlays, ...	Page 451 lines 7-11.	input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
		and to transmit these overlays to TV set, 202,	Page 26 lines 4-8.	... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first.
		upon command.	Page 44 lines 14-17.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.
			Page 26 lines 20-28.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. (Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ...
wherein said method controls displaying said video information on said remote display.	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;
			Page 37 line 26 to	In each decoder, the controller, 39, 44, or

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			page 38 line 8.	47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.
	This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.		Page 26 lines 4-11.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...
	The viewer then sees a microcomputer generated graphic of his own stocks' performance ...			
77. The method of claim 67, wherein at least one of said messages from said cable head end to	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;
			Page 37 line 26 to page 38 line 8.	In each decoder, the controller, 39, 44, or 47, receives detected digital information from

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p> <p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p>
	<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>	Page 26 lines 4-11.		
said downloaded executable program comprises a command.	Column 19 lines 48-53.	These signals instruct microcomputer, 205, to	Page 23 line 35 to page 24 line 16.	<p>Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		generate several graphic video overlays, ... and to transmit these overlays to TV set, 202, upon command.	Page 451 lines 7-11. Page 26 lines 4-8. Page 44 lines 14-17. Page 26 lines 20-28.	instructions that is loaded and run is called a "program instruction set.") ... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first. Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. (Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ...
78. The method of claim 67, wherein at least one of said messages from said cable head end to said downloaded executable program comprises an instruct-to-overlay signal.	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2. Page 37 line 26 to page 38 line 8.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205; In each decoder, the controller, 39, 44, or 47, receives detected digital information from

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p> <p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p>
	<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>		Page 26 lines 4-11.	
170. A method of controlling	Column 19 line 60 to column 20 line 1.	<p>At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.</p>	<p>Page 25 line 34 to page 26 line 2.</p> <p>Page 37 line 26 to page 38 line 8.</p>	<p>At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;</p> <p>In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38,</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>	<p>Page 26 lines 4-11.</p>	<p>43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p> <p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p>
a receiver station which includes	Column 17 lines 47-53.	<p>FIG 6 illustrates one possible configuration of equipment in a home or office or other television and/or radio receiving site. Consideration of FIGS. 6F and 6G is facilitated by consideration, first, of individual examples of the types of co-ordinated presentations that the signal apparatus and methods described here can permit.</p>	<p>Page 390 lines 30-35.</p> <p>Page 396 lines 8-10.</p>	<p>Fig. 7 exemplifies one embodiment of an ultimate receiver station; is a subscriber station in the field distribution system, 93, of the intermediate transmission station of Fig. 6; and may be a home, an office, a theater, a hotel, or any other station where programming such as television or radio is displayed to persons.</p> <p>Features, benefits, and modes of operation of the station of Fig. 7 are demonstrated in the following individual examples.</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
a television receiver,	Column 19 lines 28-29.	...and tuner, 215, to tune appropriately to "Wall Street Week."	Page 445 line 35 to page 446 line 1. Page 446 lines 17-21.	... and to tune monitor, 202M, in a predetermined fashion. In so doing, controller, 20, causes monitor, 202M, to receive the decrypted video and audio information of the "Wall Street Week" program, to display the video image of said information, and to emit sound in accordance with said audio....
a signal detector,	Column 19 lines 63-64.	This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 26 lines 1-2. Page 37 line 26 to page 38 line 8.	Said signal is identified by decoder, 203; transferred to microcomputer, 205; and ... In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus. This base band signal is then transferred through separate paths to three separate detector devices.
a processor, an output device, and with said receiver station adapted to	Column 6 lines 48-50. Column 19 lines 64-66.	This base band signal is then transmitted through separate paths to three separate detector devices. This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202,...	Page 34 line 35 to page 35 line 1. Page 26 lines 1-8.	 This base band signal is then transferred through separate paths to three separate detector devices. Said signal is identified by decoder, 203; transferred to microcomputer, 205; and executed by microcomputer, 205, at the system level as the statement, "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.
detect the presence of one or	Column 19 lines 63-66.	This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205. This signal instructs	Page 26 lines 1-8.	Said signal is identified by decoder, 203; transferred to microcomputer, 205; and executed by microcomputer, 205, at the

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		microcomputer, 205, to transmit the first overlay to TV set, 202,	Page 37 line 26 to page 38 line 8.	system level as the statement, "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to correct errors ... by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus ...
	Column 6 lines 48-50.	This base band signal is then transmitted through separate paths to three separate detector devices.	Page 34 line 35 to page 35 line 1.	This base band signal is then transferred through separate paths to three separate detector devices.
more control signals and	Column 19 lines 63-66.	This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205. This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202,	Page 26 lines 1-8.	Said signal is identified by decoder, 203; transferred to microcomputer, 205; and executed by microcomputer, 205, at the system level as the statement, "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. In each decoder, the controller, 39, 44, or 47,

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 20 lines 5-7.	... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.	page 38 line 8.	receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to correct errors ... by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus ...
			Page 27 lines 7-9 and	Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.
			Page 451 line 22 to Page 452 line 5.	Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.
programmed to process downloadable	Column 19 lines 42-44.	Microcomputer, 205, is preprogramed to respond in a predetermined fashion to instruction signals embedded in the "Wall Street Week" programing transmission.	Page 21 lines 20-24.	Microcomputer, 205, is preprogrammed to ... respond in a predetermined fashion to instruction signals embedded in the "Wall Street Week" programming transmission.
executable code, said method of controlling comprising the steps of:	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
			Page 44 lines 14-17.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a

Claim Language of Instant Application		Applicants' Priority U.S. Pat. No. '490		Instant Specification	
		Reference	Language	Reference	Language
				Page 26 lines 20-28.	(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
(1) receiving at	Column 10 lines 30-39.	The facility receives programming from many sources. Transmissions may be received from satellites by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions can be received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions can be received by antenna, 60, and TV demodulator, 61. Other electronic programming input means, 62, can receive programming transmissions.		Page 324 lines 23-31.	The station receives programming from many sources. Transmissions are received from a satellite by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions are received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions are received by antenna, 60, and TV demodulator, 61. Other electronic programming transmissions are received by other programming input means, 62.
a transmitter station	Column 10 lines 24-28.	FIGS. 3A, 3B and 3C illustrates one instance of such use. FIGS. 3A, 3B, and 3C illustrate the use of Signal Processing Apparatus and Methods at a cable television system "head end" transmission facility that cablecasts several channels of television programming.		Page 324 lines 18-21.	Fig. 6 illustrates Signal Processing Apparatus and Methods at an intermediate transmission station that is a cable television system "head end" and that cablecasts several channels of television programming.
downloadable	Column 19 lines 43-44.	... instruction signals embedded in the "Wall Street Week" programming transmission.		Page 21 lines 23-24.	... instruction signals embedded in the "Wall Street Week" programming transmission.
executable code which is effective at said receiver station	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals		Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.		detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
			Page 44 lines 14-17.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a
			Page 26 lines 20-28.	(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
to respond to	Column 19 lines 48-53.	These signals instruct microcomputer, 205, to	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p> <p>... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first.</p> <p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.</p> <p>A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions.</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ...</p>
	<p>generate several graphic video overlays, ...</p> <p>and to transmit these overlays to TV set, 202,</p> <p>upon command.</p>		<p>Page 451 lines 7-11.</p> <p>Page 26 lines 4-8.</p> <p>Page 44 lines 14-17.</p> <p>Page 26 lines 20-28.</p>	
messages	Column 2 lines 63-64.	(The term "signal unit" hereinafter means	Page 14 lines 26-27.	(The term "signal unit" hereinafter means one

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	<p><i>For example</i> Column 19 lines 64-66.</p> <p>Column 20 lines 5-7.</p>	<p>one complete signal instruction or information message unit.</p> <p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202,...</p> <p>... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.</p>	<p><i>For example</i> Page 26 lines 1-8.</p> <p>Page 27 lines 7-9 and</p> <p>Page 451 line 22 to Page 452 line 5.</p>	<p>complete signal instruction or information message unit.</p> <p>Said signal is identified by decoder, 203; transferred to microcomputer, 205; and executed by microcomputer, 205, at the system level as the statement, "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.</p> <p>Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.</p> <p>Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p> <p>In computer-based combined medium communications, the amount of information that a given system can convey is dependent</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
communicated from a broadcast or cablecast transmitter station	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programing to signal processor, 71, and signal processor, 96, ...	Page 337 lines 1-8.	Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to signal processor, 96, ...
	Column 10 lines 15-20.	The signal processing apparatus outlined in FIGS. 1, A, 2B, and 2C, and their variants as appropriate, can be used to automate the operations of an intermediate transmission point whether it be a broadcast station transmitting only a single channel of programing or a cable system cablecasting many channels.	Page 324 lines 8-17.	The signal processing apparatus outlined in Figs. 2, 2A, 2B, 2C, and 2D, and their variants as appropriate, can be used to automate the operations of intermediate transmission stations that receive and retransmit programming. The stations so automated may transmit any form of electronically transmitted programming, including television, radio, print, data, and combined medium programming and may range in scale of operation from wireless broadcast stations that transmit a single programming transmission to cable systems that cablecast many channels simultaneously.
to affect said output device,	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programing and is transmitted in the programing transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203, transferred to microcomputer, 205;
			Page 37 line 26 to page 38 line 8.	In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p>
	<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p> <p>... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.</p>		<p>Page 26 lines 4-11.</p> <p>Page 27 lines 7-9 and</p> <p>Page 451 line 22 to Page 452 line 5.</p>	<p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p> <p>Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.</p> <p>Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's</p>
	<p>Column 20 lines 5-7.</p>			

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p> <p>In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.</p>
said downloadable executable code having at said receiver station a target processor to process data;	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	<p>Page 23 line 35 to page 24 line 16.</p> <p>Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p>	
			<p>Page 44 lines 14-17.</p> <p>A command is an instance of signal</p>	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			Page 26 lines 20-28.	<p>information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)</p>
(2) transferring said downloadable executable code to a transmitter;	Column 10 lines 40-47.	<p>All of these received transmissions feed into the facility by hard-wire and connect, by means of conventional switches (here matrix switch, 75), to one or more video recorder/players, 76 and 78, and/or to equipment that outputs them over various channels to the cable system's field distribution system, 93, which equipment includes here cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>	<p>Page 324 line 31 to page 325 line 4.</p> <p>Page 21 lines 23-24.</p>	<p>Each receiver/modulator/input apparatus, 53 through 62, transfers its received transmissions into the station by hard-wire, a conventional matrix switch, 75, well known in the art, one or more recorder/players, 76 and 78, apparatus that outputs said transmissions over various channels to the cable system's field distribution system, 93, which apparatus includes cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>
(3) receiving said one or more control signals at said transmitter station,	Column 10 lines 30-39.	The facility receives programming from many sources. Transmissions may be received from satellites by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions can be received by microwave antenna, 57, and television	Page 324 lines 23-31.	The station receives programming from many sources. Transmissions are received from a satellite by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions are received by microwave antenna, 57, and television video and audio receivers, 58 and

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
downloadable executable code;		microcomputer, 205. This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202,		executed by microcomputer, 205, at the system level as the statement, "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.
			Page 37 line 26 to page 38 line 8.	In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to correct errors ... by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus ...
	Column 20 lines 5-7.	... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.	Page 27 lines 7-9 and Page 451 line 22 to Page 452 line 5.	Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions. Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p> <p>In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.</p>
(4) transferring said one or more control signals to said transmitter; and	Column 10 lines 40-47.	<p>All of these received transmissions feed into the facility by hard-wire and connect, by means of conventional switches (here matrix switch, 75), to one or more video recorder/players, 76 and 78, and/or to equipment that outputs them over various channels to the cable system's field distribution system, 93, which equipment includes here cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>	<p>Page 324 line 31 to page 325 line 4.</p> <p>Page 21 lines 23-24.</p>	<p>Each receiver/modulator/input apparatus, 53 through 62, transfers its received transmissions into the station by hard-wire, a conventional matrix switch, 75, well known in the art, one or more recorder/players, 76 and 78, apparatus that outputs said transmissions over various channels to the cable system's field distribution system, 93, which apparatus includes cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>
(5) transmitting at least one information transmission said downloadable	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and signal processor, 96, ...	Page 337 lines 1-8.	<p>Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier,</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 19 lines 43-44.	... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 21 lines 23-24.	95, inputs programming transmissions to signal processor, 96, instruction signals embedded in the "Wall Street Week" programming transmission.
executable code and	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
			Page 44 lines 14-17.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a
			Page 26 lines 20-28.	(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			<p>205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.</p> <p>In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to correct errors ... by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus ...</p> <p>Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.</p> <p>Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called</p>	
	<p>Column 20 lines 5-7.</p> <p>... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.</p>		<p>Page 37 line 26 to page 38 line 8.</p> <p>Page 27 lines 7-9 and</p> <p>Page 451 line 22 to Page 452 line 5.</p>	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
effective to control said receiver station.	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming decoder, 203, and transferred via processor, 204, to microcomputer, 205.	<p>Page 25 line 34 to page 26 line 2.</p> <p>Page 37 line 26 to page 38 line 8.</p> <p>Page 26 lines 4-11.</p>	<p>"over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p> <p>In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.</p> <p>At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;</p> <p>In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p> <p>Said signal instructs microcomputer, 205, at</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		<p>to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>		<p>the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p>
171. The method of claim 170, wherein said downloadable executable code or	Column 19 lines 46-53.	<p>When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.</p>	<p>Page 23 line 35 to page 24 line 16.</p> <p>Page 44 lines 14-17.</p>	<p>Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p> <p>A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			Page 26 lines 20-28.	(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
identification data in respect of said downloadable executable code are	Column 19 lines 14-15.	... pass all program and channel identifiers on all programming being cablecast on the multi-channel system.	Page 435 lines 16-18.	In due course, while scanning sequentially all channels in the fashion of example #5, the apparatus of the signal processor, 200, of the station of Fig. 7 and 7C ...
			Page 248 lines 22-26 from example #5.	Via a conventional multi-channel cable transmission, in a fashion well known in the art, four channels of conventional television programming and two conventional FM radio signals are inputted to a first alternate contact of switch, 1, and to mixer, 2.
			Page 250 lines 13-16 from example #5.	Example #5 begins with the embedding and transmitting, at the remote station that originates the "Wall Street Week" broadcast, of the first message of the "Wall Street Week" program ...
			Page 252 lines 15-35 from example #5.	Then, in a predetermined fashion, control processor, 39J, determines that said first command contains subject matter meter-monitor information causing said control processor, 39J, to transmit a message that consists of ... execution segment information that is addressed to microcomputer, 205, (and that causes microcomputer, 205, to process the information of the meter-monitor segment

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>immediately following said execution segment information as new programming now being transmitted on the channel of the channel mark of said meter-monitor segment) then meter-monitor segment information that includes the "program unit identification code" and subject matter information of said first command and the channel mark of cable channel 13 ... (Said message whose transmission is caused by receiving said first command enables microcomputer, 205, in a fashion described more fully below, to tune automatically to receive the program that said "program unit identification code" identifies if said program is of interest, ...</p> <p>All eight of said messages are commands. The 1st- and 3rd-new-program-message (#5) and the 1st-new-radio-program- message (#5) signals are addressed to microcomputer, 205. Each informs said microcomputer of new programming transmissions to which said microcomputer can tune appropriate station receiver and display apparatus in fashions described below. (Hereinafter said commands are called "guide commands" because they can guide station control apparatus to desired programming.)</p> <p>The present invention employs signals embedded in programming.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>
embedded in a television signal.	<p>Column 4 lines 5-6.</p> <p><i>For example</i> Column 19 lines 43-44.</p>	<p>These techniques employ signals embedded in programs.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>	<p>Page 13 lines 25-26.</p> <p><i>For example</i> Page 21 lines 23-24.</p>	<p>Page 267 lines 20-28 from example #5.</p>
172. The method of claim 170, wherein video is displayed at said receiver station and	<p>Column 19 line 64 to column 20 line 2.</p>	<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204. The</p>	<p>Page 26 lines 4-11.</p>	<p>... "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		viewer then sees a microcomputer generated graphic of his own stocks' performance overlay the studio generated graphic.	Page 451 line 3.	video information and transmit the combined information to TV monitor, 202M. TV shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And the Fig. 1C combining is displayed.
said downloadable executable code programs said receiver station processor to	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.") A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a (Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes
			Page 44 lines 14-17.	
			Page 26 lines 20-28.	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
output a first portion of said video.	Column 19 lines 48-53.			subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
		These signals instruct microcomputer, 205, to	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
		generate several graphic video overlays, ...	Page 451 lines 7-11.	... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first.
		and to transmit these overlays to TV set, 202, upon command.	Page 26 lines 4-8. Page 44 lines 14-17.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			Page 26 lines 20-28.	<p>said apparatus to perform a particular function or functions.</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ...</p>
173. The method of claim 170, further comprising the step of transmitting a second portion of said video to said receiver station.	<p>Column 12 lines 45-47.</p> <p>Column 19 line 53-56.</p>	<p>Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and signal processor, 96, ...</p> <p>Subsequently in the program, the host says, "Here is what the Dow Jones Industrials did is the past week," and a studio generated graphic is pictured.</p>	<p>Page 337 lines 1-8.</p> <p>Page 25 lines 26-33.</p>	<p>Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to signal processor, 96, ...</p> <p>During this time the program may show the so-called "talking head" of the host as he describes the behavior of the stock market over the course of the week. Then the host says, "Now as we turn to the graphs, here is what the Dow Jones Industrials did in the week just past," and a studio generated graphic is transmitted. Fig. 1B shows the image of said graphic as it appears on the video screen of TV monitor, 202M.</p>
176. The method of claim 170, further comprising the step of	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and	Page 337 lines 1-8.	Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		The viewer then sees a microcomputer generated graphic of his own stocks' performance ...		displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...
205. A method of controlling	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2. Page 37 line 26 to page 38 line 8. Page 26 lines 4-11.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203, transferred to microcomputer, 205; In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus. Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
a plurality of receiver stations each of which includes		The viewer then sees a microcomputer generated graphic of his own stocks' performance ...		the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...
	Column 3 lines 48-51.	Another method has application at receiver sites such as private homes or public places like theaters, hotels, brokerage offices, etc., whether commercial establishments or not.	Page 12 lines 30-35.	It is the further purpose of this invention to provide means and methods for the automation of ultimate receiver stations, ... Such ultimate receiver stations may be private homes or offices or commercial establishments such as theaters, hotels, or brokerage offices.
	<i>For example</i> Column 17 lines 47-53.	FIG 6 illustrates one possible configuration of equipment in a home or office or other television and/or radio receiving site. Consideration of FIGS. 6F and 6G is facilitated by consideration, first, of individual examples of the types of co-ordinated presentations that the signal apparatus and methods described here can permit.	<i>For example</i> Page 390 lines 30-35. Page 396 lines 8-10.	Fig. 7 exemplifies one embodiment of an ultimate receiver station; is a subscriber station in the field distribution system, 93, of the intermediate transmission station of Fig. 6; and may be a home, an office, a theater, a hotel, or any other station where programming such as television or radio is displayed to persons. Features, benefits, and modes of operation of the station of Fig. 7 are demonstrated in the following individual examples.
a television receiver,	Column 19 lines 27-29.	...and also microcomputer, 205, may instruct switch, 216, to turn TV set, 202, on and tuner, 215, to tune appropriately to "Wall Street Week."	Page 445 line 24 to page 446 line 1. Page 446 lines 17-21.	... instructions causes controller, 20, to switch power on to monitor, 202M, and commence transferring the television output transmission of microcomputer, 205, to said monitor, 202M; ... Automatically, controller, 20, inputs a particular instruction to decoder, 145, via said communications link, that causes decoder, 145, to switch power on to monitor, 202M, and to tune monitor, 202M, in a predetermined fashion. In so doing, controller, 20, causes monitor, 202M, to receive the decrypted video and audio information of the "Wall Street Week" program, to display the video image of said information, and to emit sound in accordance

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
a signal detector,	Column 19 lines 63-64.	This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	with said audio ... Page 26 lines 1-2. Page 37 line 26 to page 38 line 8.	Said signal is identified by decoder, 203; transferred to microcomputer, 205; and ... In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.
a processor, and with each said receiver station adapted to	Column 6 lines 48-50. Column 19 lines 63-66.	This base band signal is then transmitted through separate paths to three separate detector devices. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205. This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202,	Page 34 line 35 to page 35 line 1. Page 26 lines 1-8. Page 37 line 26 to page 38 line 8.	This base band signal is then transferred through separate paths to three separate detector devices. Said signal is identified by decoder, 203; transferred to microcomputer, 205; and executed by microcomputer, 205, at the system level as the statement, "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to correct errors ... by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art into digital information that subscriber

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus ...
detect the presence of each of a plurality of control signals and	Column 6 lines 48-50.	This base band signal is then transmitted through separate paths to three separate detector devices.	Page 34 line 35 to page 35 line 1.	This base band signal is then transferred through separate paths to three separate detector devices.
	Column 19 lines 63-66.	This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205. This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202,	Page 26 lines 1-8.	Said signal is identified by decoder, 203; transferred to microcomputer, 205; and executed by microcomputer, 205, at the system level as the statement, "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.
	Column 20 lines 5-7.	... and [microcomputer, 205,] prepares to send the next locally generated graphic	Page 37 line 26 to page 38 line 8.	In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to correct errors ... by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus ...
			Page 27 lines 7-9 and	Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		overlay upon instruction from the originating studio.	Page 451 line 22 to Page 452 line 5.	to operate under control of received instructions. Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient. In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.
programmed to process downloadable processor instructions, said method comprising the steps of:	Column 19 lines 42-44.	Microcomputer, 205, is preprogrammed to respond in a predetermined fashion to instruction signals embedded in the "Wall Street Week" programing transmission.	Page 21 lines 20-24.	Microcomputer, 205, is preprogrammed to ... respond in a predetermined fashion to instruction signals embedded in the "Wall Street Week" programming transmission.
	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p> <p>A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)</p>
			<p>Page 44 lines 14-17.</p> <p>Page 26 lines 20-28.</p>	
(1) receiving at	Column 10 lines 30-39.	The facility receives programing from many sources. Transmissions may be received from satellites by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56.	Page 324 lines 23-31.	The station receives programming from many sources. Transmissions are received from a satellite by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions are

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		<p>Microwave transmissions can be received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions can be received by antenna, 60, and TV demodulator, 61. Other electronic programming input means, 62, can receive programming transmissions.</p>		<p>received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions are received by antenna, 60, and TV demodulator, 61. Other electronic programming transmissions are received by other programming input means, 62.</p>
a transmitter station	Column 10 lines 24-28.	<p>FIGS. 3A, 3B and 3C illustrates one instance of such use. FIGS. 3A, 3B, and 3C illustrate the use of Signal Processing Apparatus and Methods at a cable television system "head end" transmission facility that cablecasts several channels of television programming.</p>	Page 324 lines 18-21.	<p>Fig. 6 illustrates Signal Processing Apparatus and Methods at an intermediate transmission station that is a cable television system "head end" and that cablecasts several channels of television programming.</p>
said downloadable processor instructions	Column 19 lines 43-44.	<p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>	Page 21 lines 23-24.	<p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>
which are effective at a receiver station, when executed, to operate a computer under	Column 19 lines 48-53.	<p>These signals instruct microcomputer, 205, to</p> <p>generate several graphic video overlays, ...</p>	<p>Page 23 line 35 to page 24 line 16.</p> <p>Page 451 lines 7-11.</p>	<p>Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p> <p>... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first.</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		and to transmit these overlays to TV set, 202, upon command.	Page 26 lines 4-8. Page 44 lines 14-17. Page 26 lines 20-28.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. (Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes a subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ...
broadcast or cablecast network	Column 10 lines 15-20. Column 15 lines 57-62.	The signal processing apparatus outlined in FIGS. 1, A, 2B, and 2C, and their variants as appropriate, can be used to automate the operations of an intermediate transmission point whether it be a broadcast station transmitting only a single channel of programming or a cable system cablecasting many channels. The signals for which the decoders are monitoring are likely to be unique digital codes that may identify each programming or data unit received and the source of each. They may identify networks,	Page 324 lines 8-17. Page 315 lines 20-24.	The signal processing apparatus outlined in Figs. 2, 2A, 2B, 2C, and 2D, and their variants as appropriate, can be used to automate the operations of intermediate transmission stations that receive and retransmit programming. The stations so automated may transmit any form of electronically transmitted programming, including television, radio, print, data, and combined medium programming and may range in scale of operation from wireless broadcast stations that transmit a single programming transmission to cable systems that cablecast many channels simultaneously. Each one of said decoders is preprogrammed to detect and transfer to said onboard controller, 14, via said bus means, the meter-monitor information of every unencrypted SPAM message in the

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490	Reference	Language	Instant Specification	Language
			broadcast stations, channels on cable systems, and possibly times of transmission.	Page 44 lines 26-32.	transmission to which its associated apparatus is tuned. Commands often contain meter-monitor segments. Said segments contain meter information and/or monitor information, and the information of said segments causes subscriber station signal processor systems to assemble, record, and transmit meter records to remote billing stations and monitor records to remote ratings stations in fashions that are described more fully below.
				Page 49 line 26 to Page 50 line 4.	Meter-monitor segments contain meter information and/or monitor information. Examples of categories of such information include: ... unique codes for programming; ... and unique codes that identify the sources and suppliers of computer data. ... origins of transmissions (eg., network source stations, broadcast stations, cable head end stations); dates and times monitor information that identifies what programming is available, ...
control, said downloadable processor instructions having at each of said plurality of receiver stations	Column 19 line 60 to column 20 line 1.		At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2. Page 37 line 26 to page 38 line 8.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205; In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller 39 is

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>	<p>Page 26 lines 4-11.</p>	<p>preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p> <p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p>
a target processor to process data;	Column 19 line 64 to column 20 line 1.	<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204. The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>	Page 26 lines 4-10.	<p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the ...</p>
(2) transferring said downloadable processor instruction to a transmitter;	Column 10 lines 40-47.	All of these received transmissions feed into the facility by hard-wire and connect, by means of conventional switches (here matrix switch, 75), to one or more video recorder/players, 76 and 78, and/or to equipment that outputs them over various	Page 324 line 31 to page 325 line 4.	<p>Each receiver/modulator/input apparatus, 53 through 62, transfers its received transmissions into the station by hard-wire, a conventional matrix switch, 75, well known in the art, one or more recorder/players, 76 and 78, apparatus that outputs said transmissions</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 19 lines 43-44.	channels to the cable system's field distribution system, 93, which equipment includes here cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92. ... instruction signals embedded in the "Wall Street Week" programing transmission.	Page 21 lines 23-24. ... instruction signals embedded in the "Wall Street Week" programming transmission.	over various channels to the cable system's field distribution system, 93, which apparatus includes cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92. ... instruction signals embedded in the "Wall Street Week" programming transmission.
(3) receiving said plurality of control signals at said transmitter station,	Column 10 lines 30-39.	The facility receives programing from many sources. Transmissions may be received from satellites by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions can be received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions can be received by antenna, 60, and TV demodulator, 61. Other electronic programing input means, 62, can receive programing transmissions. ... instruction signals embedded in the "Wall Street Week" programing transmission.	Page 324 lines 23-31. Page 21 lines 23-24.	The station receives programming from many sources. Transmissions are received from a satellite by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions are received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions are received by antenna, 60, and TV demodulator, 61. Other electronic programming transmissions are received by other programming input means, 62. ... instruction signals embedded in the "Wall Street Week" programming transmission.
wherein each of said plurality of control signals operates to execute a different one of	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programing and is transmitted in the programing transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2. Page 37 line 26 to page 38 line 8.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205; In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p>
	<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>		<p>Page 26 lines 4-11.</p>	<p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p>
	<p>... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.</p>		<p>Page 27 lines 7-9 and</p>	<p>Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.</p>
	<p>Column 20 lines 5-7.</p>		<p>Page 451 line 22 to Page 452 line 5.</p>	<p>Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
said downloadable processor instructions; and	Column 19 lines 48-53.			<p>and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p> <p>In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.</p>
	These signals instruct microcomputer, 205, to		Page 23 line 35 to page 24 line 16.	<p>Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p>
	generate several graphic video overlays, ...		Page 451 lines 7-11.	<p>... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first.</p>
	and to transmit these overlays to TV set, 202,		Page 26 lines 4-8.	<p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		upon command.	<p>Page 44 lines 14-17.</p> <p>Page 26 lines 20-28.</p>	<p>A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions.</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ...</p>
(4) transferring said plurality of control signals to said transmitter, and	<p>Column 10 lines 40-47.</p> <p>Column 19 lines 43-44.</p>	<p>All of these received transmissions feed into the facility by hard-wire and connect, by means of conventional switches (here matrix switch, 75), to one or more video recorder/players, 76 and 78, and/or to equipment that outputs them over various channels to the cable system's field distribution system, 93, which equipment includes here cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>	<p>Page 324 line 31 to page 325 line 4.</p> <p>Page 21 lines 23-24.</p>	<p>Each receiver/modulator/input apparatus, 53 through 62, transfers its received transmissions into the station by hard-wire, a conventional matrix switch, 75, well known in the art, one or more recorder/players, 76 and 78, apparatus that outputs said transmissions over various channels to the cable system's field distribution system, 93, which apparatus includes cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>
transmitting an information transmission comprising	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and signal processor, 96, ...	Page 337 lines 1-8.	<p>Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 19 lines 43-44.	... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 21 lines 23-24.	signal processor, 96, instruction signals embedded in the "Wall Street Week" programming transmission.
said downloadable processor instructions and	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.") A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a (Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the
			Page 44 lines 14-17.	
			Page 26 lines 20-28.	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
said plurality of control signals;	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.		above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
			Page 25 line 34 to page 26 line 2. Page 37 line 26 to page 38 line 8.	At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203, transferred to microcomputer, 205; In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.
		This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204. The viewer then sees a microcomputer	Page 26 lines 4-11.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 20 lines 5-7.	<p>generated graphic of his own stocks' performance ...</p> <p>... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.</p>	<p>Page 27 lines 7-9 and</p> <p>Page 451 line 22 to Page 452 line 5.</p>	<p>subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p> <p>Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.</p> <p>Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p> <p>In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.</p>
wherein said method controls said plurality of receiver stations.	Column 19 line 60 to column 20 line 1.	<p>At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to</p>	Page 25 line 34 to page 26 line 2.	<p>At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		microcomputer, 205.	Page 37 line 26 to page 38 line 8.	In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.
		This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.	Page 26 lines 4-11.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...
		The viewer then sees a microcomputer generated graphic of his own stocks' performance ...		
206. The method of claim 205, wherein said downloadable processor instructions and	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205,

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
said plurality of control signals are	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to	<p>evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p> <p>A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)</p> <p>At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203, transferred to microcomputer, 205;</p>	
			<p>Page 44 lines 14-17.</p> <p>Page 26 lines 20-28.</p>	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		microcomputer, 205.	Page 37 line 26 to page 38 line 8.	In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.
		This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.	Page 26 lines 4-11.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...
	Column 20 lines 5-7.	... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.	Page 27 lines 7-9 and	Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.
			Page 451 line 22 to Page 452 line 5.	Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p> <p>In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.</p>
embedded in a television signal.	Column 19 lines 43-44.	... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 21 lines 23-24.	... instruction signals embedded in the "Wall Street Week" programming transmission.
207. The method of claim 205, wherein video is displayed at a receiver station and	Column 19 line 64 to column 20 line 2.	This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204. The viewer then sees a microcomputer generated graphic of his own stocks' performance overlay the studio generated graphic.	Page 26 lines 4-11. Page 451 line 3.	<p>... "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic.</p> <p>And the Fig. 1C combining is displayed.</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
said downloadable processor instructions program said processor of said receiver station to	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
			Page 44 lines 14-17.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a
			Page 26 lines 20-28.	(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
output a first portion of said video, said method further comprising the step of	Column 19 lines 48-53.	These signals instruct microcomputer, 205, to	Page 23 line 35 to page 24 line 16.	particular combining.) Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.") ... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first. Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. (Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the
		generate several graphic video overlays, ...	Page 451 lines 7-11.	
		and to transmit these overlays to TV set, 202,	Page 26 lines 4-8.	
		upon command.	Page 44 lines 14-17.	
			Page 26 lines 20-28.	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				above program instruction set provide another example of a combining synchronizing command ...
transmitting a second portion of said video to said receiver station.	Column 12 lines 45-47. Column 19 line 53-56.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and signal processor, 96, ... Subsequently in the program, the host says, "Here is what the Dow Jones Industrials did is the past week," and a studio generated graphic is pictured.	Page 337 lines 1-8. Page 25 lines 26-33.	Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to signal processor, 96, ... During this time the program may show the so-called "talking head" of the host as he describes the behavior of the stock market over the course of the week. Then the host says, "Now as we turn to the graphs, here is what the Dow Jones Industrials did in the week just past," and a studio generated graphic is transmitted. Fig. 1B shows the image of said graphic as it appears on the video screen of TV monitor, 202M.
208. The method of claim 205, wherein a period of time separates	Column 19 lines 67 to column 20 line 2.	The viewer then sees a microcomputer generated graphic of his own stocks' performance overlay the studio generated graphic.	Page 451 line 3. Page 26 lines 8-11.	And the Fig. 1C combining is displayed. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic.
transmission of a first and	Column 19 lines 60-63.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission.	Page 59 lines 29-33.	A SPAM message is the modality whereby the original transmission station that originates said message controls specific addressed apparatus at subscriber stations. The information of any given SPAM transmission consists of a series or stream of sequentially

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			<p>transmitted SPAM messages.</p> <p>At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted.</p> <p>The second message is of the information associated with the second combining synch command. Said second command has a "00" header, an execution segment, and a meter-monitor ...</p>	
a second of at least two of said plurality of control signals.	Column 20 lines 5-7.	... and [microcomputer, 205,] prepares to send the next locally generated graphic overlay upon instruction from the originating studio.	<p>Page 25 line 34 to page 26 line 1.</p> <p>Page 90 lines 4-7. Applicants teach this as the composition of the instruction signal of page 25 line 34. See page 26 lines 1-4 and 20-28, page 89 lines 3-6, and page 90 lines 4-11.</p> <p>Page 27 lines 7-9 and</p> <p>Page 451 line 22 to Page 452 line 5.</p>	<p>Thereafter the "Wall Street Week" program proceeds, and microcomputer, 205, continues to operate under control of received instructions.</p> <p>Furthermore, it is undesirable to separate computer operations merely because they result in the generation of separate overlays because such separation may result in unnecessary duplication of calculations. For example, the Fig. 1C display of user specific overall stock portfolio performance could be followed by second and third displays that analyze portions of the subscriber's portfolio--eg., the portion invested in New York Stock Exchange listed stocks in comparison to the so-called "NYSE" index and the portion invested in so-called "over-the-counter" stocks in comparison to the so-called "NASDAQ" index. In order to calculate the value of the overall portfolio, it is necessary to calculate the value of these portions. To require that the values of the portions be recalculated for subsequent overlays would be inefficient.</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				In computer-based combined medium communications, the amount of information that a given system can convey is dependent on the efficiency of the employment of program instruction sets and combining synch commands.
315. A method of controlling	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	<p>Page 25 line 34 to page 26 line 2.</p> <p>Page 37 line 26 to page 38 line 8.</p> <p>Page 26 lines 4-11.</p>	<p>At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;</p> <p>In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p> <p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then</p>
		This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.		

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		The viewer then sees a microcomputer generated graphic of his own stocks' performance ...		displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...
a plurality of receiver stations each of which includes	Column 3 lines 48-51. <i>For example</i> Column 17 lines 47-53.	Another method has application at receiver sites such as private homes or public places like theaters, hotels, brokerage offices, etc., whether commercial establishments or not. FIG 6 illustrates one possible configuration of equipment in a home or office or other television and/or radio receiving site. Consideration of FIGS. 6F and 6G is facilitated by consideration, first, of individual examples of the types of co-ordinated presentations that the signal apparatus and methods described here can permit.	Page 12 lines 30-35. <i>For example</i> Page 390 lines 30-35. Page 396 lines 8-10.	It is the further purpose of this invention to provide means and methods for the automation of ultimate receiver stations, ... Such ultimate receiver stations may be private homes or offices or commercial establishments such as theaters, hotels, or brokerage offices. Fig. 7 exemplifies one embodiment of an ultimate receiver station; is a subscriber station in the field distribution system, 93, of the intermediate transmission station of Fig. 6; and may be a home, an office, a theater, a hotel, or any other station where programming such as television or radio is displayed to persons. Features, benefits, and modes of operation of the station of Fig. 7 are demonstrated in the following individual examples.
a television receiver,	Column 19 lines 27-29.	...and also microcomputer, 205, may instruct switch, 216, to turn TV set, 202, on and tuner, 215, to tune appropriately to "Wall Street Week."	Page 445 line 24 to page 446 line 1. Page 446 lines 17-21.	... instructions causes controller, 20, to switch power on to monitor, 202M, and commence transferring the television output transmission of microcomputer, 205, to said monitor, 202M; ... Automatically, controller, 20, inputs a particular instruction to decoder, 145, via said communications link, that causes decoder, 145, to switch power on to monitor, 202M, and to tune monitor, 202M, in a predetermined fashion. In so doing, controller, 20, causes monitor, 202M, to receive the decrypted video and audio information of the "Wall Street Week" program, to display the video image of said

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus ...
data, each said plurality of receiver stations is adapted to	Column 19 lines 35-41.	Each weekday, microcomputer, 205, receives, about 4:30 PM, by means of a digital information channel, all closing stock prices applicable that day. It may receive these directly or it may automatically query a data service for them in a predetermined fashion. It records those prices that relate to the stocks in its stored portfolio.	Page 449 lines 13-35.	Each weekday after 4:30 PM, a remote stock-price-data- transmission station transmits all closing stock price data applicable that day and causes apparatus at each subscriber station, in a predetermined fashion, to select and record at the microcomputer, 205, of said station the particular closing price datum or data that apply to the particular stock or stocks of the preprogrammed portfolio of said computer. (Said remote station transmits said closing stock price data and causes specific subscriber stations to select and process their specific information of interest in the fashion in which remote news-service-A station transmitted the AT&T news item and caused selected stations to select and process, in their specific fashions, the information of said item.) Alternatively, microcomputer, 205, is caused in a predetermined fashion (for example, by a SPAM message a given transmission monitored by signal processor, 200, in any of the above described fashions) automatically to telephone a remote data service computer, by means of network, 262, in a fashion well known in the art, and to cause said remote computer to select and transmit the particular closing price datum or data of the stock or stocks of the portfolio of said microcomputer, 205, thereby causing said microcomputer, 205, to record said datum or data in a predetermined fashion.
detect at least one	Column 6 lines 48-50.	This base band signal is then transmitted	Page 34 line 35 to page	This base band signal is then transferred

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
control signal and	Column 19 lines 63-66.	through separate paths to three separate detector devices. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205. This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202,	35 line 1. Page 26 lines 1-8. Page 37 line 26 to page 38 line 8.	through separate paths to three separate detector devices. Said signal is identified by decoder, 203; transferred to microcomputer, 205; and executed by microcomputer, 205, at the system level as the statement, "GRAPHICS ON". Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed ... to correct errors ... by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus ...
	Column 19 lines 42-44.	Microcomputer, 205, is preprogramed to respond in a predetermined fashion to instruction signals embedded in the "Wall Street Week" programing transmission.	Page 21 lines 20-24.	Microcomputer, 205, is preprogrammed to ... respond in a predetermined fashion to instruction signals embedded in the "Wall Street Week" programming transmission.
programmed to process downloadable processor instructions, said method comprising the steps of:	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.		signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
			Page 44 lines 14-17.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a
			Page 26 lines 20-28.	(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
(1) receiving at	Column 10 lines 30-39.	The facility receives programing from many sources. Transmissions may be received from satellites by satellite antenna,	Page 324 lines 23-31.	The station receives programming from many sources. Transmissions are received from a satellite by satellite antenna, 50, low noise

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		and to transmit these overlays to TV set, 202, upon command.	Page 26 lines 4-8. Page 44 lines 14-17. Page 26 lines 20-28.	of Fig. 1C is merely the first. Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. (Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes a subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ...
(2) transferring said downloadable processor instructions to a transmitter; signal.	Column 10 lines 40-47. Column 19 lines 43-44.	All of these received transmissions feed into the facility by hard-wire and connect, by means of conventional switches (here matrix switch, 75), to one or more video recorder/players, 76 and 78, and/or to equipment that outputs them over various channels to the cable system's field distribution system, 93, which equipment includes here cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92. ... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 324 line 31 to page 325 line 4. Page 21 lines 23-24.	Each receiver/modulator/input apparatus, 53 through 62, transfers its received transmissions into the station by hard-wire, a conventional matrix switch, 75, well known in the art, one or more recorder/players, 76 and 78, apparatus that outputs said transmissions over various channels to the cable system's field distribution system, 93, which apparatus includes cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92. ... instruction signals embedded in the "Wall Street Week" programming transmission.
(3) receiving said at least one control	Column 10 lines 30-39.	The facility receives programming from many sources. Transmissions may be	Page 324 lines 23-31.	The station receives programming from many sources. Transmissions are received from a

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
signal at said transmitter station,	Column 19 lines 43-44.	<p>received from satellites by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions can be received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions can be received by antenna, 60, and TV demodulator, 61. Other electronic programming input means, 62, can receive programming transmissions.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>	<p>satellite by satellite antenna, 50, low noise amplifiers, 51 and 52, and TV receivers, 53, 54, 55, and 56. Microwave transmissions are received by microwave antenna, 57, and television video and audio receivers, 58 and 59. Conventional TV broadcast transmissions are received by antenna, 60, and TV demodulator, 61. Other electronic programming transmissions are received by other programming input means, 62.</p> <p>... instruction signals embedded in the "Wall Street Week" programming transmission.</p>	
wherein said at least one control signal operates to execute	Column 19 line 60 to column 20 line 1.	<p>At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.</p>	<p>At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;</p> <p>In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p>	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>	Page 26 lines 4-11.	<p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...</p>
said downloadable processor instructions; and	Column 19 lines 48-53.	<p>These signals instruct microcomputer, 205, to</p> <p>generate several graphic video overlays, ...</p> <p>and to transmit these overlays to TV set, 202,</p> <p>upon command.</p>	<p>Page 23 line 35 to page 24 line 16.</p> <p>Page 451 lines 7-11.</p> <p>Page 26 lines 4-8.</p> <p>Page 44 lines 14-17.</p>	<p>Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p> <p>... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first.</p> <p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.</p> <p>A command is an instance of signal</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. (Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ...
(4) transferring said at least one control signal to said transmitter, and	Column 10 lines 40-47.	All of these received transmissions feed into the facility by hard-wire and connect, by means of conventional switches (here matrix switch, 75), to one or more video recorder/players, 76 and 78, and/or to equipment that outputs them over various channels to the cable system's field distribution system, 93, which equipment includes here cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92. ... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 26 lines 20-28. Page 324 line 31 to page 325 line 4. Page 21 lines 23-24.	Each receiver/modulator/input apparatus, 53 through 62, transfers its received transmissions into the station by hard-wire, a conventional matrix switch, 75, well known in the art, one or more recorder/players, 76 and 78, apparatus that outputs said transmissions over various channels to the cable system's field distribution system, 93, which apparatus includes cable channel modulators, 83, 87, and 91, and channel combining and multiplexing system, 92. ... instruction signals embedded in the "Wall Street Week" programming transmission.
transmitting at least one information transmission comprising	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and signal processor, 96, ...	Page 337 lines 1-8.	Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to signal processor, 96, ...

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 19 lines 43-44.	... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 21 lines 23-24.	... instruction signals embedded in the "Wall Street Week" programming transmission.
said downloadable processor instructions and	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
			Page 44 lines 14-17.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a
			Page 26 lines 20-28.	(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command in

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
said at least one control signal.	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	<p>Page 25 line 34 to page 26 line 2.</p> <p>Page 37 line 26 to page 38 line 8.</p> <p>Page 26 lines 4-11.</p>	<p>that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)</p> <p>At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205;</p> <p>In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus.</p> <p>Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the subscriber's own portfolio performance overlaid on the studio generated graphic. And</p>
		<p>This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.</p> <p>The viewer then sees a microcomputer generated graphic of his own stocks' performance ...</p>		

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				microcomputer, 205, commences ...
316. The method of claim 315, further comprising the steps of: embedding at least one of	Column 4 lines 5-6.	These techniques employ signals embedded in programs.	Page 13 lines 25-26.	The present invention employs signals embedded in programming.
(i) said downloadable processor instructions and	Column 19 lines 43-44.	... instruction signals embedded in the "Wall Street Week" programming transmission.	Page 21 lines 23-24.	... instruction signals embedded in the "Wall Street Week" programming transmission.
(ii) identification data with respect to said downloadable processor instructions in	Column 19 lines 14-15.	... pass all program and channel identifiers on all programming being cablecast on the multi-channel system.	Page 435 lines 16-18.	In due course, while scanning sequentially all channels in the fashion of example #5, the apparatus of the signal processor, 200, of the station of Fig. 7 and 7C ...
			Page 248 lines 22-26 from example #5.	Via a conventional multi-channel cable transmission, in a fashion well known in the art, four channels of conventional television programming and two conventional FM radio signals are inputted to a first alternate contact of switch, 1, and to mixer, 2.
			Page 250 lines 13-16 from example #5.	Example #5 begins with the embedding and transmitting, at the remote station that originates the "Wall Street Week" broadcast, of the first message of the "Wall Street Week" program ...
			Page 252 lines 15-35 from example #5.	Then, in a predetermined fashion, control processor, 39J, determines that said first command contains subject matter meter-monitor information causing said control processor, 39J, to transmit a message that consists of ... execution segment information that is addressed to microcomputer, 205, (and that causes microcomputer, 205, to process the information of the meter-monitor segment

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
				<p>immediately following said execution segment information as new programming now being transmitted on the channel of the channel mark of said meter-monitor segment) then meter-monitor segment information that includes the "program unit identification code" and subject matter information of said first command and the channel mark of cable channel 13 ... (Said message whose transmission is caused by receiving said first command enables microcomputer, 205, in a fashion described more fully below, to tune automatically to receive the program that said "program unit identification code" identifies if said program is of interest, ...</p> <p>All eight of said messages are commands. The 1st- and 3rd-new-program-message (#5) and the 1st-new-radio-program- message (#5) signals are addressed to microcomputer, 205. Each informs said microcomputer of new programming transmissions to which said microcomputer can tune appropriate station receiver and display apparatus in fashions described below. (Hereinafter said commands are called "guide commands" because they can guide station control apparatus to desired programming.)</p>
			Page 267 lines 20-28 from example #5.	
a signal that includes a television program; and	Column 19 lines 20-23.	Analyzing these identifier signals in a predetermined fashion, microcomputer, 205, determines that "Wall Street Week" is being televised on channel X.	Page 267 lines 20-28 from example #5.	<p>All eight of said messages are commands. The 1st- and 3rd-new-program-message (#5) and the 1st-new-radio-program- message (#5) signals are addressed to microcomputer, 205. Each informs said microcomputer of new programming transmissions to which said microcomputer can tune appropriate station receiver and display apparatus in fashions described below. (Hereinafter said commands are called "guide commands" because they can guide station control apparatus to desired programming.)</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490 Reference	Language	Instant Specification Reference	Language
			<p>Page 435 lines 16-25.</p> <p>Page 436 line 9 to page 437 line 3.</p>	<p>In due course, while scanning sequentially all channels in the fashion of example #5, the apparatus of the signal processor, 200, of the station of Fig. 7 and 7C detects one instance of the Select-WSW-Program-Unit SPAM message of the station of Fig. 6 ...</p> <p>Receiving said Select-WSW-Program-Unit message causes the apparatus of said signal processor, 200, to input said message to the microcomputer, 205, of said station.</p> <p>Receiving said Select-WSW-Program-Unit message causes decoder, 203, ... to input ... the information segment of said message to the CPU of microcomputer, 205, and to cause said CPU to execute the information so inputted as a machine language job. The information so inputted is the aforementioned determine-whether-to-select instructions that contain said particular specific-WSW information and said please-fully-enable-WSW-on-CC13-at-particular-8:30 information.</p> <p>Executing said determine-whether-to-select instructions causes microcomputer, 205, to ... Said instructions contain one instance, and ... program-unit-of-interest information that is preprogrammed at said microcomputer, 205, contains a second instance of specific-WSW information, <i>which second instance reflects the wish of the subscriber of said station to view (or record) said "Wall Street Week" program when said program is transmitted.</i> Automatically, microcomputer, 205, compares said one instance to said program-unit-of-interest information and determines a match with said second instance.</p> <p>Determining a match causes microcomputer, 205, automatically to input said please-fully-enable-WSW-on-CC13-at-particular- 8:30 information to the controller, 20.</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			Page 439 lines 14-15.	...to receive the transmission of cable channel 13;...
transmitting said signal that includes a television program.	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and signal processor, 96, ...	Page 337 lines 1-8.	Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to signal processor, 96, ...
317. The method of claim 315, wherein a television program is displayed at a receiver station of said plurality of receiver stations and	Column 19 lines 27-29.	...and also microcomputer, 205, may instruct switch, 216, to turn TV set, 202, on and tuner, 215, to tune appropriately to "Wall Street Week."	Page 445 line 24 to page 446 line 1.	... instructions causes controller, 20, to switch power on to monitor, 202M, and commence transferring the television output transmission of microcomputer, 205, to said monitor, 202M; ... Automatically, controller, 20, inputs a particular instruction to decoder, 145, via said communications link, that causes decoder, 145, to switch power on to monitor, 202M, and to tune monitor, 202M, in a predetermined fashion.
			Page 446 lines 17-21.	In so doing, controller, 20, causes monitor, 202M, to receive the decrypted video and audio information of the "Wall Street Week" program, to display the video image of said information, and to emit sound in accordance with said audio ...
	Column 19 line 53-56.	Subsequently in the program, the host says, "Here is what the Dow Jones Industrials did is the past week," and a studio generated graphic is pictured.	Page 25 lines 26-33.	During this time the program may show the so-called "talking head" of the host as he describes the behavior of the stock market over the course of the week. Then the host says, "Now as we turn to the graphs, here is what the Dow Jones Industrials did in the

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
said downloadable processor instructions program said processor at said receiver station of said plurality of receiver stations to	Column 19 lines 46-53.	When the "Wall Street Week" transmission begins at 8:30 PM on a Friday evening, several instruction signals are identified by decoder, 203, and transferred to microcomputer, 205. These signals instruct microcomputer, 205, ... upon command.	Page 23 line 35 to page 24 line 16.	<p>week just past," and a studio generated graphic is transmitted. Fig. 1B shows the image of said graphic as it appears on the video screen of TV monitor, 202M.</p> <p>Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions that follows said word or words just as the information of a file named FILE.EXE, recorded on the contained floppy disk, would be loaded at RAM (from the input buffer to which the disk drive of said disk inputs) and run were the command "FILE" entered from the console keyboard to the system level of the installed disk operating system. (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")</p> <p>A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions. A command is always constituted of at least a</p> <p>(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another</p>
			Page 44 lines 14-17.	
			Page 26 lines 20-28.	

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
output a video portion of said television program.	Column 19 lines 48-53.			example of a combining synch command in that said word or words synchronized all subscriber station computers in commencing loading and running information for a particular combining.)
		These signals instruct microcomputer, 205, to	Page 23 line 35 to page 24 line 16.	Subsequently, a second series of instructions is embedded and transmitted at said program originating studio. Said second series is detected and converted into usable digital signals by decoder, 203, and inputted to microcomputer, 205, in the same fashion as the first series. Microcomputer, 205, evaluates the initial signal word or words which instruct it to load at RAM (from the input buffer to which decoder, 203, inputs) and run the information of a particular set of instructions ... (Hereinafter, such a set of instructions that is loaded and run is called a "program instruction set.")
		generate several graphic video overlays, ...	Page 451 lines 7-11.	... the program instruction set in the first message of the "Wall Street Week" example instructs microcomputer, 205, to generate not one but a plurality overlays. The combining of Fig. 1C is merely the first.
		and to transmit these overlays to TV set, 202,	Page 26 lines 4-8.	Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M.
		upon command.	Page 44 lines 14-17.	A command is an instance of signal information that is addressed to particular subscriber station apparatus and that causes said apparatus to perform a particular function or functions.
			Page 26 lines 20-28.	(Hereinafter, an instruction such as the above signal of "GRAPHICS ON" that causes

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
	Column 19 line 60 to column 20 line 1.	At this point, an instruction signal is generated in the television studio originating the programming and is transmitted in the programming transmission. This signal is identified by decoder, 203, and transferred via processor, 204, to microcomputer, 205.	Page 25 line 34 to page 26 line 2. Page 37 line 26 to page 38 line 8.	subscriber station apparatus to execute a combining operation in synchronization is called a "combining synch command." Said initial signal word or words that preceded the above program instruction set provide another example of a combining synch command ... At this point, an instruction signal is generated at said program originating studio, embedded in the programming transmission, and transmitted. Said signal is identified by decoder, 203; transferred to microcomputer, 205; In each decoder, the controller, 39, 44, or 47, receives detected digital information from the relevant detector or detectors, 34, 37, 38, 43, and 46. Upon receiving any given instance of signal information, controller, 39, 44, or 47, is preprogrammed to process said information automatically. Controller, 39, is preprogrammed to ... correct errors in retained received information by means of forward error correction techniques well known in the art; to convert, as may be required, the corrected information, by means of input protocol techniques well known in the art, into digital information that subscriber station apparatus can receive and process; ... to identify in a predetermined fashion or fashions subscriber station apparatus to which said signal information should be transferred; and to transfer said signals to said apparatus. Said signal instructs microcomputer, 205, at the PC-MicroKey 1300 to overlay the graphic information in its graphics card onto the received composite video information and transmit the combined information to TV monitor, 202M. TV monitor, 202M, then displays the image shown in Fig. 1C which is the microcomputer generated graphic of the
		This signal instructs microcomputer, 205, to transmit the first overlay to TV set, 202, for as long as it receives the same instruction signal from processor, 204.	Page 26 lines 4-11.	
		The viewer then sees a microcomputer		

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
		generated graphic of his own stocks' performance ...		subscriber's own portfolio performance overlaid on the studio generated graphic. And microcomputer, 205, commences ...
318. The method of claim 317, further comprising the step of transmitting said television program.	Column 12 lines 45-47.	Beyond channel combining system and multiplexer, 92, amplifier, 94, transmits programming to signal processor, 71, and signal processor, 96, ...	Page 337 lines 1-8.	Fig. 6 shows particular signal processor system monitoring apparatus associated with the intermediate station of Fig. 6. In field distribution system, 93, amplifier, 94, inputs programming transmissions to signal processor system, 71, (where said transmissions are inputted to one alternate contact of the switch, 1, of the signal processor of said system, 71), and amplifier, 95, inputs programming transmissions to signal processor, 96, ...
	Column 19 lines 20-23.	Analyzing these identifier signals in a predetermined fashion, microcomputer, 205, determines that "Wall Street Week" is being televised on channel X.	Page 267 lines 20-28 from example #5. Page 435 lines 16-25.	<p>All eight of said messages are commands. The 1st- and 3rd-new-program-message (#5) and the 1st-new-radio-program-message (#5) signals are addressed to microcomputer, 205. Each informs said microcomputer of new programming transmissions to which said microcomputer can tune appropriate station receiver and display apparatus in fashions described below. (Hereinafter said commands are called "guide commands" because they can guide station control apparatus to desired programming.)</p> <p>In due course, while scanning sequentially all channels in the fashion of example #5, the apparatus of the signal processor, 200, of the station of Fig. 7 and 7C detects one instance of the Select-WSW-Program-Unit SPAM message of the station of Fig. 6 ...</p> <p>Receiving said Select-WSW-Program-Unit message causes the apparatus of said signal processor, 200, to input said message to the microcomputer, 205, of said station.</p>

Claim Language of Instant Application	Applicants' Priority U.S. Pat. No. '490		Instant Specification	
	Reference	Language	Reference	Language
			Page 436 line 9 to page 437 line 3.	<p>Receiving said Select-WSW-Program-Unit message causes decoder, 203, ... to input ... the information segment of said message to the CPU of microcomputer, 205, and to cause said CPU to execute the information so inputted as a machine language job. The information so inputted is the aforementioned determine-whether-to-select instructions that contain said particular specific-WSW information and said please-fully-enable-WSW-on-CC13-at-particular-8:30 information.</p> <p>Executing said determine-whether-to-select instructions causes microcomputer, 205, to ... Said instructions contain one instance, and ... program-unit-of-interest information that is preprogrammed at said microcomputer, 205, contains a second instance of specific-WSW information, <i>which second instance reflects the wish of the subscriber of said station to view (or record) said "Wall Street Week" program when said program is transmitted.</i> Automatically, microcomputer, 205, compares said one instance to said program-unit-of-interest information and determines a match with said second instance.</p> <p>Determining a match causes microcomputer, 205, automatically to input said please-fully-enable-WSW-on-CC13-at-particular- 8:30 information to the controller, 20.</p> <p>...to receive the transmission of cable channel 13;...</p>
			Page 439 lines 14-15.	